

BELASTNINGSKRAV????



Risteopbygning:

Kantstål : 20x5 mm.

Bærestave : 40x5 mm. m/udklinkning

Støttestave: 2 stk. 20x3 mm.

Fyldestave : 16x3 mm.

09.03.17	Tegning for godkendelse/kommentarer	DM
Date	Description	Init.
	PcP.A/S Sverigesvej 2-4 T: +45 97 13 12 00 DK-7480 Vildbjerg F: +45 97 13 35 25	member of 
Type: Polysan - 498x177x20 mm. PcP Gitterriste Ma33/Mc33 40x5/20x5 mm. - m/2 stk. støttestave 20x3 mm.		
Material: St. 240 YP	Surface: Galv.	Scale: 1:5
Weight:		
<small>FPC og WPS i henhold til EN 1090-1:2009/A1-2 EXC 2 i henhold til DS/EN ISO 3834-3:2006 Svejsning, tolerancer i henhold til DS/EN ISO 5817:2014 niveau C Calkansereti i henhold til DS/EN ISO 1461:2009 Tolerancer overflader P1 i henhold til DS/EN ISO 8501-1:2007 Mål uden tolerance i henhold til DS/ISO 2768 (PFG Norm) Alle mål i mm.</small>		PcP Dwg. no.: <b>D-113212-28</b> Rev. no.: <b>01</b>

This drawing is the property of PcP A/S, and is not to be reproduced or used in any manner detrimental to our interests. All rights are reserved.